



TECHNICAL DATA SHEET
Dalton Foundation Coating
Manufacturer Product#: 3055



PHYSICAL PROPERTIES & PERFORMANCE

Appearance: Thick brown liquid. Dries black.	Maximum VOC: Less than 25 g/L
Application Temperature: 55° F and rising.	Specific Gravity: 1.3-1.5
Viscosity: 5,000-15,000 cps	Weight Per Gallon: 9.2 lbs. per gallon
Color: Brown in liquid state. Dries black.	Consistency: Thick liquid.
Boiling Point: >212° F	Cure Time (50% relative humidity, 70° F): 24-48 hours.
Freeze ability: Do not allow to freeze.	Container Size & Weight: 4.75gallons, Approximately 55 lbs.

FEATURES

Dalton Enterprises Foundation Coating is an asphalt emulsion based dampproofer designed for exterior use in above and below-grade applications. Dalton Foundation Coating is an advanced formula that contains polymer additives for long lasting strength and flexibility.

Features:

- Polymer fortified for strength and flexibility
- Meets Requirements in ASTM D-1227-95 for Type II Class I
- Crack Resistant formula
- Low odor, easy soap and water clean up
- Non-Flammable when wet
- Low VOC formula
- Apply with roller or roofing brush

**Note: Product dries black...is brown only in liquid form.*

COVERAGE

Coverage per 4.75gal pail is approximately 125 sq. ft. for one coat. Coverage rates vary depending upon the condition of the existing surface.

SURFACE PREPARATION

Brush off dust and loose particles and scrub stains/rust spots with wire brush. Rinse well. Allow all repaired surfaces to cure 24 hours prior to sealing. Complete surface preparations and allow area to completely dry (24 hours recommended).

APPLICATION

DO NOT DILUTE. Apply coating on clear day only when air temperature is 50° F *and* rising and rain is not likely for 36 hours. Also, do not apply very late in the day.

Stir

Stirring may be needed to obtain a uniform mix. Normally the pails will only need a quick mix but to be sure it's good idea to flip over the pail at least 24 hours prior to using the product. (Carefully inspect the lid to insure it is secure before turning over).

Drying

Let product dry completely between coats. Typically dries within 8 hours in warm and dry weather conditions and within 2 to 7 days in cooler or humid weather. Allow to cure for one to two days before backfilling if used on below grade walls or foundations.

PRECAUTIONS

Avoid applying coating during rain and when temperatures drop below 55° F. When transporting this product, ensure that the container is secured and the lid is secure. Do not allow the container to tumble as this may loosen the lid and allow leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Protective clothing and eyewear should be used during application.

CLEAN UP & STORAGE

While wet, clean up with soap and water. If dry, scrub with citrus based cleaner or mineral spirits. Containers are recyclable. Do not heat or store container in temperatures above 110° F. **KEEP FROM FREEZING!** Product is Non-Hazardous.

!CAUTION!

CAUTION! HARMFUL OR FATAL IF SWALLOWED!

Dalton Foundation Coating is for exterior use only. Keep out of reach of children. Keep container capped when not in use.

Emergency & First Aid Procedures:

Eyes: Immediately flush with clean water for 15 minutes while holding eyelids open; consult a physician.

Inhalation: If overcome by mist or vapor, remove from exposure immediately; call a physician. If breathing is stopped or irregular, start resuscitation, administer oxygen.

Skin: Remove any contaminated clothing and wash skin with soap and warm water. Vegetable or mineral oil can remove dry material.

Ingestion: **DO NOT INDUCE VOMITING** even though vomiting may occur. If vomiting occurs, keep head below hips

Dalton Enterprises, Inc., 131 Willow Street, Cheshire, CT 06410

Phone 800-851-5606 • Fax (203) 271-3396 • www.latexite.com

Revised 09/09/17

to prevent aspiration of liquid into the lungs. Get immediate medical attention.

Non-flammable. This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARRANTY AND DISCLAIMER

There are no express warranties which extend beyond the description on the face hereof. DALTON ENTERPRISES, INC. DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY, OR OF FITNESS FOR ANY PARTICULAR PURPOSE. Since seller cannot control the manner of use of its products after their sale, seller will not be responsible for any consequential or indirect damages. Rather, seller will, at its options, either replace the goods sold or refund the purchase price. No warranties will apply if the goods are in any way altered or modified after delivery by seller. This warranty does not include labor or cost of labor for the application or consequential damages. This warranty gives you specific rights and you may also have other rights which may vary from state to state.