



## TECHNICAL DATA SHEET

### Latex·ite™ 4.75gal. Color Grade™ Driveway Filler / Sealer...for blacktop



DOVER GREY MODEL #:11320, UPC#: 090932113206  
NATURAL BEIGE MODEL #:11310, UPC#: 090932113107  
BRICK RED MODEL #: 11300, UPC#: 090932113008

## PHYSICAL PROPERTIES

<b>Appearance:</b> Liquid (Red looks orange in wet form but will dry brick red)	<b>Maximum VOC:</b> <b>Less than 10 g/L</b>
<b>Application Temperature:</b> 55°F and rising	<b>Specific Gravity:</b> 1.3-1.5
<b>Viscosity:</b> 5,000-10,000	<b>Weight Per Gallon:</b> 10.8-11.6 lbs. per gallon
<b>Color:</b> Red, Beige, Gray	<b>Consistency:</b> liquid
<b>Boiling Point:</b> ≥212° F	<b>Cure Time (50% relative humidity, 70°F, 21.1°C):</b> 2 hours foot traffic or 2 <sup>nd</sup> coat, 24hours car traffic
<b>Freeze ability:</b> <b>Do not allow to freeze.</b>	<b>Container Size &amp; Weight:</b> 4.75 gallons, Approximately 52 lbs.

## FEATURES

Latex·ite® Color Grade™ Driveway Filler / Sealer is a ready-to-use, high performance, water based blacktop driveway sealer (NOT FOR CONCRETE) that will beautify and protect the entrance to your home. Customers have asked for a color sealant for their blacktop walkways and driveways...so here it is! Color Grade™ is a durable, tinted filler/sealer that resists hot tire pick-up, chemicals and leaves a non-skid finish. It is available in three colors: Natural Beige, Dover Grey and Brick Red. The temperature of the blacktop will certainly be reduced by using a lighter shade like the grey or beige. Our recent test on Beige showed an 18 degrees F reduction versus the blacktop.

- Resists Hot Tire Pick Up
- Fortified, Non-Skid
- UV Protected
- Low VOC, Easy Clean-Up
- Apply with Seal Right Squeegee (Roller is wrong applicator and voids warranty)
- A free mix kit ships with every order to ensure consistent color

## SURFACE PREPARATION

Sweep and clean off entire driveway using Latex·ite® CLEANER/DEGREASER. Scrub oil, gas spots, stains and rinse with water. Apply Latex·ite® OIL SPOT PRIMER to any oil spots/stains using a paint brush. Allow Latex·ite® OIL SPOT PRIMER to dry  $\frac{1}{2}$  hour prior to sealing over. If pavement is extremely hot, apply a fine water mist prior to sealing; brush out any remaining puddles. You can edge the driveway with a large paint or wall paper brush by dipping brush into sealer and slowly edging the driveway (put a tarp over any concrete areas so you don't accidentally get sealer onto concrete). Allow all Latex·ite® patch and repair products to fully cure overnight before applying sealer. Newly paved surfaces must cure for a minimum of 12 months.

## APPLICATION

**DO NOT DILUTE SEALER.** Apply sealer only when ground temperature is 55° F *and* rising and rain is not likely for 24 hours. Early spring or late fall application when sun is at a low angle can prevent sealer from curing properly which may cause tracking.

1. Please flip pails over the night prior to use to make for easier stirring next day. On day of project make sure to have an empty 5gallon pail as we recommend intermixing pails to ensure uniform color and consistency. We include a free mix kit with every order to make the project easier for you.
2. Allow first coat to dry before applying second coat. A second coat is required to achieve color uniformity. DO NOT APPLY MORE THAN TWO COATS.
3. Use a squeegee to apply Color Grade™ (NO rollers) and maintain a wet edge of bead when applying (ie don't let it 'run out' before you pour more down).
4. It is important to complete each coat in one continuous application to prevent color shading. Stir pails during project. **Note: COLORS MAY VARY SLIGHTLY FROM PAIL LABEL COLOR.**
5. Wait at least 30 days before rinsing or cleaning. Use a mild detergent as needed. Areas that have scuffed can be cleaned with soap, water and brush after 30 days. Use only a mild or diluted soap/detergent. The use of pressure washers and abrasive cleaners should be limited to avoid sealer failure.

## PRECAUTIONS

Avoid applying sealer when rainfall is likely within 24 hours of application time. Avoid applying sealer when temperatures drop below 55° F. Allow all repaired surfaces to cure 24 hours prior to sealing. For crack fillers you should wait 24 hours. If the crack filler is firm you may seal over. When transporting this product, ensure that the container is secured and the lid is secure. Do not allow the container to tumble as this may loosen the lid and allow leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Protective clothing and eyewear should be used during application.

## CLEAN UP & STORAGE

While wet, clean up with soap and water. If dry, scrub with citrus based cleaner. Containers are recyclable. Do not heat or store container in temperatures above 110° F. **KEEP FROM FREEZING!** Product is Non-Hazardous.

## !CAUTION!

### **Color Grade™ is for exterior use only. Keep out of reach of children.**

Keep container capped when not in use. Non-flammable. This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

#### **Emergency & First Aid Procedures:**

**Eyes:** Immediately flush with clean water for 15 minutes while holding eyelids open; consult a physician.

**Inhalation:** If overcome by mist or vapor, remove from exposure immediately; call a physician. If breathing is stopped or irregular, start resuscitation, administer oxygen.

**Skin:** Remove any contaminated clothing and wash skin with soap and warm water. Vegetable or mineral oil can remove dry material.

**Ingestion:** DO NOT INDUCE VOMITING even though vomiting may occur. If vomiting occurs, keep head below hips to prevent aspiration of liquid into the lungs. Get immediate medical attention.

## WARRANTY AND DISCLAIMER

The methods and techniques described herein represent some that have been used successful to obtain the desired results. See label application, touch up and clean up instructions. Allow new blacktop to fully cure-we recommend 12 months prior to sealing. If water “beads up” on blacktop, it has not fully cured. All variations in blacktop, climate conditions and equipment cannot be anticipated by Dalton Enterprises. The decision to use any of these methods and techniques is entirely at the election and responsibility of the user. Sealer is warranted from defects for a period of one year from date of purchase when applied according to our application instructions. Two coats are necessary for warranty to apply. Since seller cannot control the manner of use of its products after their sale, seller will not be responsible for any consequential or indirect damages. Dalton will not be liable for areas that have ponding waters, poor drainage or snow removal damage. If product is deemed defective, it shall be replaced by Dalton. No warranties will apply if goods in any way altered or modified after delivery by seller. There are no express warranties which extend beyond the description on the face hereof, manufacturer disclaims any implied warranties. This warranty does not include labor cost incurred for the application, re-application or consequential damage costs. Failures due acts of God, fire, structural defects or causes beyond our control are excluded from this warranty. If repair products were used, Latex•ite® repair products must be used for warranty to be honored. Two coats must be applied to validate warranty. Not applicable on commercial parking lots. This warranty gives you specific rights and you may also have other rights which may vary from state to state. Original proof of purchase required for warranty claims.