



# Line Paint Product Specification

## Description and Usage

Latexite® Line Paint is a heavily pigmented, high solid, 100% acrylic paint. It is designed for use over bituminous concrete (asphalt) or portland cement (concrete) recreational surfaces. Latexite® Line Paint is intended for line striping tennis, basketball, volleyball, or any other recreational court surface.

## Coverage

Coverage will be approximately .05 gal. per sq. yd., per application (180 sq. feet per gallon). Approximately one gallon of Latexite® Line Paint is required per standard U.S.T.A. sanctioned tennis court.

	Undiluted Material Per Sq. Yard
Line Paint	.05

## Drying Time

Line Paint must be allowed to dry thoroughly between coating applications. Completed projects should be allowed 24 hours to cure before releasing to play.

## Mix Design

Latex-ite® Line Paint is packaged ready to use and requires NO DILUTION. However, the product should be thoroughly mixed prior to application. A mechanical mixer is recommended.

## Application

The surface upon which Latex-ite® Line Paint is to be applied to must be smooth, free of dirt, loose or flaking paint, oily materials or chemical residues, vegetation of any sort, and any other debris or foreign matter that may prevent the proper product adhesion. Taping and priming prior to striping is recommended for best results. Using a striping roller or brush, apply tape to both sides of the area to be striped. Overlap the inside edges of the tape. This will seal the tape to the acrylic surface and prevent the Latex-ite® Line Paint from bleeding under the tape.

## Features and Benefits

- Fast Drying
- Remains Flexible
- Hi Build Paint For Crisp Lines
- Fully Pigmented, 100% Acrylic

## Limitations and Precautions

- Latex-ite® Line Paint should not be applied when ambient temperature is below 50° F or when surface temperature is above 140° F.
- Do not apply when rain is imminent.
- Do not store in direct sunlight.
- Keep from freezing.
- Latex-ite® Line Paint should be allowed to cure for 24 hours before courts are opened for use.
- New asphalt should cure for at least 14 days; concrete shall cure for 28 days.
- Concrete must be acid washed and sealed prior to coating with Latex-ite® Line Paint
- Latex-ite® Line Paint will not prevent structural cracking from occurring.
- Do Not apply over Coal Tar emulsions