

MATERIAL SAFETY DATA SHEET

FRANKLIN PAINT COMPANY INC.
WHITE CHLORINATED RUBBER TP

LOW VOC

Date Printed: 3/27/2014
Date Revised:
Page 1 of 5

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT CODE: 2040F

PRODUCT NAME: WHITE CHLORINATED RUBBER TP

HMIS CODES: H F R P
2 3 0 X

MANUFACTURE'S NAME: FRANKLIN PAINT COMPANY INC.
ADDRESS: 259 COTTAGE STREET
FRANKLIN, MA 02038

EMERGENCY PHONE : 1-800-255-3924
INFORMATION PHONE : 1-508-528-0303

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

| Component/Exposure Limits | CAS# | % by Wt. Max |
|--------------------------------------|------------|--------------|
| CALCIUM CARBONATE | 471-34-1 | 50.02 |
| ACGIH TLV 10mg/m3 AS DUST | | |
| OSHA PEL 15 mg/m3 TOTAL DUST | | |
| OSHA PEL 5 mg/m3 RESPIRABLE FRACTION | | |
| * ACETONE | 67-64-1 | 17 |
| OSHA VPEL 750 PPM-TWA | | |
| OSHA VPEL 1000 PPM-STEL | | |
| ACGIH TLV 500 PPM-TWA | | |
| ACGIH TLV 750 PPM-STEL | | |
| TITANIUM DIOXIDE | 13463-67-7 | 7.65 |
| ACGIH TLV 10 mg/m3 AS DUST | | |
| OSHA PEL 10 mg/m3 TOTAL DUST | | |
| OSHA PEL 5 mg/m3 RESPIRABLE FRACTION | | |
| * VM&P NAPHTHA | 64742-48-9 | 6 |
| OSHA PEL TWA 300 PPM; STEL 400 PPM | | |
| ACGIH TLV TWA 300 PPM | | |
| ETHYL ALCOHOL | 64-17-5 | .33 |
| OSHA PEL 1000 PPM-TWA | | |
| ACGIH TLV 1000 PPM-TWA | | |

SECTION 3 - HAZARDS IDENTIFICATION

Potential Health Effects

EYE: LIQUID OR VAPOR CONTACT MAY CAUSE IRRITATION.

SKIN: SKIN IRRITANT.

INGESTION: THIS MATERIAL MAY BE HARMFUL OR FATAL IF SWALLOWED. IRRITATING TO MOUTH, THROAT, LUNG AND STOMACH.

INHALATION: SYMPTOMS MAY INCLUDE: STOMACH OR INTESTINAL UPSET (NAUSEA, VOMITING, DIARRHEA) IRRITATION (NOSE, THROAT, AIRWAYS), CENTRAL NERVOUS SYSTEM DEPRESSION (DIZZINESS, DROWSINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS),

MATERIAL SAFETY DATA SHEET

FRANKLIN PAINT COMPANY INC.
WHITE CHLORINATED RUBBER TP

LOW VOC

Date Printed: 3/27/2014
Date Revised:
Page 2 of 5

LOSS OF APPETITE, LOSS OF COORDINATION, IRREGULAR HEARTBEAT, NARCOSIS (DAZED OR SLUGGISH FEELING), AND DEATH.

SECTION 4 - FIRST AID MEASURE

EYES: FLUSH EYES THOROUGHLY WITH A LARGE AMOUNT OF WATER. SEEK MEDICAL ATTENTION.

SKIN: WASH OFF IMMEDIATELY WITH SOAP AND WATER. IF SKIN IRRITATION OCCURS SEEK MEDICAL ATTENTION.

INGESTION: DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION IMMEDIATELY.

INHALATION: IF AFFECTED, REMOVE FROM EXPOSURE, RESTORE BREATHING, KEEP WARM AND QUIET. SEEK MEDICAL ATTENTION IMMEDIATELY.

NOTE TO PHYSICIANS: TREAT SYMPTOMATICALLY.

SECTION 5 - FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

FLASH POINT: -4 F METHOD: TCC

FLAMMABLE LIMITS:

Lower flammable limit: .9 Upper flammable limit: 12.8

AUTOIGNITION TEMPERATURE: 869 F

HAZARDOUS COMBUSTION PRODUCTS: UNDER FIRE CONDITIONS SOME COMPONENTS OF THIS PRODUCT MAY DECOMPOSE. THE SMOKE MAY CONTAIN UNIDENTIFIED TOXIC AND/OR IRRITATING COMPOUNDS. COMBUSTION PRODUCTS MAY INCLUDE AND ARE NOT LIMITED TO: CARBON MONOXIDE. CARBON DIOXIDE. OXIDES OF NITROGEN.

EXTINGUISHING MEDIA: DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATER FOG, HALON.

UNUSUAL FIRE AND EXPLOSION HAZARDS: REMOVE ALL SOURCES OF IGNITION.

FIREFIGHTING INSTRUCTIONS: WEAR FULL PROTECTIVE CLOTHING, INCLUDING SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FULLY INVOLVED FIRES.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SMALL SPILL: REMOVE SOURCES OF IGNITION. COLLECT ON INERT ABSORBENT.

LARGE SPILL: REMOVE SOURCES OF IGNITION. CONTAIN SPILL IF POSSIBLE. REMOVE MECHANICALLY (BY PUMPING). USE EXPLOSION-PROOF EQUIPMENT. COLLECT IN SUITABLE

MATERIAL SAFETY DATA SHEET

FRANKLIN PAINT COMPANY INC.
WHITE CHLORINATED RUBBER TP

LOW VOC

Date Printed: 3/27/2014
Date Revised:
Page 3 of 5

AND PROPERLY LABELED CONTAINERS.

SECTION 7 - HANDLING AND STORAGE

HANDLING: KEEP CONTAINER TIGHTLY CLOSED. ENSURE AREA IS WELL VENTILATED. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

STORAGE: DO NOT STORE ABOVE 120 DEGREES F. CONTENTS ARE EXTREMELY FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. VAPORS WILL ACCUMULATE READILY AND MAY IGNITE EXPLOSIVELY. KEEP OUT OF THE REACH OF CHILDREN.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: LOCAL VENTILATION OF EMISSION SOURCES MAY BE NECESSARY TO MAINTAIN AMBIENT CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS.

RESPIRATORY PROTECTION: USE NIOSH APPROVED ORGANIC VAPOR/DUST RESPIRATOR IF VAPORS EXCEED TLV OR PEL.

SKIN PROTECTION: WEAR SOLVENT RESISTANT GLOVES.

EYE PROTECTION: WEAR CHEMICAL SPLASH GOGGLES.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 131 F
MELTING POINT: 210 F
VAPOR PRESSURE: 30.8 kPa @ 77 F
VAPOR DENSITY: 2.0 (AIR=1)
SOLUBILITY IN WATER: NO.
SPECIFIC GRAVITY: 1.51
pH: N/A.
ODOR: CHARACTERISTIC SOLVENT ODOR.
APPEARANCE: CORRESPONDING COLOR IN LIQUID FORM.
COATING VOC: 1.25 lb/gal
MATERIAL VOC: 0.8335 lb/gal

SECTION 10 - STABILITY AND REACTIVITY

CHEMICAL STABILITY (CONDITIONS TO AVOID): AVOID HEAT, SPRARKS, OPEN FLAME AND OTHER IGNITION SOURCES.

INCOMPATIBILITY: KEEP AWAY FROM STRONG OXIDIZING AGENTS, HEAT AND OPEN FLAMES.

MATERIAL SAFETY DATA SHEET

FRANKLIN PAINT COMPANY INC.
WHITE CHLORINATED RUBBER TP

LOW VOC

Date Printed: 3/27/2014
Date Revised:
Page 4 of 5

HAZARDOUS DECOMPOSITION PRODUCTS: NORMAL PRODUCTS OF COMBUSTION, INCLUDING:
CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION 11 - TOXICOLOGICAL INFORMATION

EYE: MAY CAUSE EYE IRRITATION. MAY CAUSE CORNEAL INJURY.

SKIN: LD50 RABBIT, RELATED TO SUBSTANCE: ACETONE >20,000 mg/kg

INGESTION: LD50 RAT, RELATED TO SUBSTANCE: ACETONE 5,800 mg/kg

INHALATION: LC50 RAT, RELATED TO SUBSTANCE: ACETONE >16,000 ppm 4 H

CHRONIC/CARCINOGENICITY:

TERATOLOGY:

REPRODUCTION:

MUTAGENICITY:

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: GOOD PRACTICE DOES NOT ALLOW MATERIAL TO
CONTAMINATE GROUND WATER SYSTEM.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE/PROVINCIAL AND LOCAL LAWS AND
REGULATIONS.

SECTION 14 - TRANSPORT INFORMATION: (Not meant to be all inclusive)

DOT PROPER SHIPPING NAME: PAINT FLAMMABLE LIQUID. PACKING GROUP: II

DOT HAZARD CLASS: 3

RESPONSE GUIDE PAGE: 128

SECTION 15 - REGULATORY INFORMATION (Not meant to be all inclusive - selected regulations re

U.S. FEDERAL REGULATIONS: ALL CHEMICALS IN THIS PRODUCT ARE LISTED, OR ARE
EXEMPT FROM LISTING ON THE TSCA INVENTORY.

CERCLA: SARA HAZARD CATEGORY: THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE

MATERIAL SAFETY DATA SHEET

FRANKLIN PAINT COMPANY INC.
WHITE CHLORINATED RUBBER TP

LOW VOC

Date Printed: 3/27/2014
Date Revised:
Page 5 of 5

EPA HAZARD CATEGORIES PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:

SARA SECTION 312:

| CHEMICAL NAME: | CAS NUMBER |
|----------------|------------|
| ACETONE | 67-64-1 |

SARA SECTION 313:

INTERNATIONAL REGULATIONS:

CANADIAN WHMIS: THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA):

EINECS:

STATE REGULATIONS: AS FOLLOWS-

SECTION 16 - OTHER INFORMATION

MSDS Status: The information contained herein relates only to the specific material identified. Franklin Paint Company believes that such information is accurate and reliable as of the date of this material safety data sheet, but no representation, guarantee or warranty, express or implied, is made as to the accuracy, reliability, or completeness of the information. Franklin Paint Company urges persons receiving this information to make their own determination as to the information's suitability and completeness for their particular application.