Dalton Enterprises, Inc. Product: Latex-ite™ Acrylic Crack Filler SDS Date: 11/03/2014

Phone: (203) 272-3221



SAFETY DATA SHEET



Section I - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Latexite® Acrylic Crack Filler

ITEM #: 3026

PACKAGE SIZE: 5 gallon pail

MANUFACTURER NAME: Dalton Enterprises, Inc. ADDRESS: 131 Willow Street, Cheshire, CT 06410 **EMERGENCY PHONE NUMBER:** (203) 272-3221

AFTER 5 PM AND ON WEEKENDS: (203) 272-3221

ORIGINATOR: RL

TRADE NAMES & SYNONYMS: Exterior Flat Latex Paint

CHEMICAL FAMILY: Blacktop coatings/sealant (water based acrylic paint)

EFFECTIVE DATE: 11/03/2014 **SUPERCEDES:** 06/17/2010

Section II - HAZARDS IDENTIFICATION

Emergency Overview: Signal Word: Warning



HCS Pictogram:

Emergency Overview: Use ventilation necessary to keep exposures below recommended exposure limits, if any.

Potential Health Effects:

Eye contact overexposure: Slight irritation. Trace amounts of amine and residual monomer vapors may be irritating to the eyes, especially in poorly ventilated areas. Irritation in the form of redness, tearing and/or blurred vision. Vapors can cause severe conjunctivitis.

Skin contact overexposure: Prolonged or repeated skin contact can cause the following:

Skin irritation, based on sensitization

Ingestion: Substance may be harmful if swallowed.

Inhalation: Inhalation of vapor or mist can cause the following:

Dizziness, weakness, fatigue, nausea, headache, irritation of the nose, throat, and lungs.

HMIS Ratings: Health: 1 Fire: 0 Reactivity 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

Dalton Enterprises, Inc.

Product: Latex-ite™ Acrylic Crack Filler

Phone: (203) 272-3221 SDS Date: 11/03/2014

Section III - COMPOSITION

CAS#	Component	Weight % less than
65996-61-4	Cellulosic Fibers	5-15%
Proprietary	Synthetic Resin	80-90%

Section IV - FIRST-AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES:

Eyes: If material splashes into eyes, immediately flush eyes with water and rinse for at least 15 minutes holding eyelids open. Get medical attention.

Skin: Remove contaminated clothing. Wash immediately with soap and water. Get medical attention if rash or irritation develops.

Ingestion: If swallowed, give 2 glasses of water to drink. DO NOT INDUCE VOMITING. Consult a physician. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Seek medical attention.

Section V - FIRE-FIGHTING MEASURES

Flash Point: Non – Combustible.

Hazardous Combustion Products: Oxides of carbon, hydrogen sulfide and sulfur oxides.

Extinguishing Media: Dry chemical, carbon dioxide, foam and water fog.

Unusual Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flame and ignition sources at locations distant from the handling point. Never use a welding or cutting torch on or near container (even empty) because vapors may ignite.

F. Lower explosive limit: Not applicable, Upper explosive limit: Not applicable

Fire Fighting Equipment/Instructions: Firefighters should wear full protective clothing including self contained breathing apparatus.

Dalton Enterprises, Inc. Product: Latex-ite™ Acrylic Crack Filler

Phone: (203) 272-3221 SDS Date: 11/03/2014

NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Section VI - ACCIDENTAL RELEASE MEASURES

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Contain spill. If spilled in an enclosed area, ventilate. Cool material to solidify. Wear proper personal protective clothing and equipment. Do not flush liquid in public sewer, water systems or surface waters. Recover as much as possible and absorb remainder with an inert material. Place into labeled closed containers and store in safe locations for proper disposal. Wash spilled areas with soap and water.

Section VII - HANDLING AND STORAGE

Handling Procedures: Wash thoroughly after using/handling. Wash hands before eating. Avoid eye contact.

Section VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION





Personal protective equipment pictograms:

Exposure Limit Information

	PEL (8hr)	STEL (15min)
1. Polymers:	None	None
2. Monomers	Not required	Not required
3. Water	None	None

PERSONAL PROTECTIVE EQUIPMENT:

Eves/Face: Use safety eyewear to prevent splashes.

Skin: Use gloves to prevent skin prolonged skin contact. Impervious / neoprene gloves are recommended. **Respiratory:** Product is to be applied outdoors but when workplace conditions warrant a respirator's use - it

must meet OSHA 1910.134.

General: Nearby eye-wash fountain recommended

Hygienic controls: Wash thoroughly with soap and water before eating or drinking.

Engineering Controls: Use only in well ventilated areas.

Dalton Enterprises, Inc. Product: Latex-ite™ Acrylic Crack Filler

Phone: (203) 272-3221 SDS Date: 11/03/2014

Section IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Viscous Black/Brown fluid **Odor:** Mild **Physical State:** Liquid **ph:** 7.5-9.5

Vapor Pressure:N/AVapor Density:WaterBoiling Point:212°FMelting Point:NDSolubility (H20):100%Specific Gravity:1.18Evaporation Rate:Slower than ether% Volatility:71.21

Octanol/H2O Coeff.: ND Flash Point: N/A

Flash Point Method: ND Upper Flammability Limit (UFL): ND

Lower Flammability Limit (LFL): ND

Burning Rate: ND

Auto Ignition: ND

Section X - STABILITY AND REACTIVITY

Chemical Stability: This is a stable material.

Chemical Stability: Conditions to Avoid: Avoid contact with strong acid and strong bases.

Incompatibility: Strong oxidizers, strong acids and strong alkalis.

Hazardous Decomposition: By open flame carbon monoxide and carbon dioxide.

Possibility of Hazardous Reactions: Will not occur.

Stability: This product is stable under normal storage conditions.

Section XI - TOXICOLOGICAL INFORMATION

NO DATA AVAILIBLE

Section XII - ECOLOGICAL INFORMATION

Ecological Fate:

Persistence/Degradability

Bioaccumulation Potential:

Mobility in Soil:

No data available

No data available

No data available

Analysis for ecological effects has not been conducted.

Section XIII - DISPOSAL CONSIDERATIONS

Disposal Instructions: All wastes must be handled in accordance with local, state and federal regulations.

Section XIV - TRANSPORTATION INFORMATION

US DOT Shipping Name: Paint **DOT Technical Name:** N.A

DOT Hazard Class: Not regulated

Dalton Enterprises, Inc. Product: Latex-ite™ Acrylic Crack Filler

Phone: (203) 272-3221 SDS Date: 11/03/2014

Section XV - REGULATORY INFORMATION

This product contains no chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community-Right-To-Know Act of 1986 and of 40 CFR 372.

Section XVI - OTHER INFORMATION

Other Precautions:

Keep out of reach of children.

Always read label plus precautions and follow directions carefully.

Use only with adequate ventilation.

Do not take internally.

Avoid contact with eyes and skin.

Wash thoroughly after using.

Do not freeze.

Revision date: 11/03/2014 **Supersedes:** 06/17/2010

Prepared by: RL

Disclaimer/Statement of Liability:

THE INFORMATION AND RECOMMENDATIONS PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMENDATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND THIS CORPORATION DISCLAIMS ANY AND ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME.

Key/Legend

EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; NJTSR = New Jersey Trade Secret Registry.