



Technical Data

GATOR-PATCH™ FOR "ALLIGATORRED" ASPHALT

General Application and Product Specification

- Designed especially for "Alligator-cracked" asphalt
- Fills & resurfaces
- Less costly than hot mix skin patching
- Ready to use-easy to apply (just pour it on – smooth it out)
- VOC = <100grams/liter



DESCRIPTION & USES

GATOR-PATCH™ is a ready-to-use blend of asphalt emulsion, mineral fillers, glass fiber, ground rubber and plasticizer designed especially to repair and restore cracked asphalt surfaces such as parking lots, driveways, walk ways, etc. Aids in preventing water seeping into the cracks that can cause extensive damage to such areas.

The use of GATOR-PATCH™ to resurface alligatored areas offers a low cost alternative to removing and replacing such areas with hot mix asphalt or hot mix "skin patching".

GATOR-PATCH™ can also be used to fill shallow depressions, or to fill cracks in excess of ½" wide in asphalt surfaces.

It is recommended that areas repaired with GATOR-PATCH™ be sealed with an asphalt protective coating to add additional protection and extend the service life of the pavement. Both coal tar emulsion sealers and asphalt-based sealers are compatible with cured GATOR-PATCH™.



APPLICATION

Surface must be dry and clean – free from all loose material, dirt and dust.

Mix GATOR-PATCH™, (a Jiffy Mixer Impellar and electric drill will aid in mixing) pour on and work in with squeegee. Prime old oxidized surfaces with Oxi-Bond™ Primer.

Apply on “Alligator Cracked” surfaces with a squeegee.

Fill depressions over ¼” deep in multiple applications of no more than ¼” at a time, allowing each coat to dry thoroughly.

Fill wide cracks and scrape off excess from the surface with a V-shaped crack squeegee.

GATOR-PATCH™ will set under good drying conditions in several hours, depending on weather and material thickness

COVERAGE

Approximately 20-50 sq.ft. per gallon for patching alligatored areas up to ¼” depth. Approximately 150 linear feet per gallon for cracks ½” x ½”.

PRECAUTIONS

Do not apply when ambient or pavement temperatures are below 50°F or are expected to drop below 50°F within 24 hours of application. Avoid application when rain is forecast within 24 hours. **KEEP FROM FREEZING.** Container should be closed when not in use. **KEEP OUT OF REACH OF CHILDREN.** Wash tools with water while material is still wet.

PACKAGING

In 5-gallon plastic pails.

ALWAYS READ THE LABEL BEFORE ATTEMPTING TO USE THE PRODUCT: Additional Technical Data Sheets and/or Material Safety Data Sheets (M.S.D.S.) are available upon request.

NOTICE: The methods and techniques described in application specifications represent some that have been used successfully to obtain the desired results. All variations in asphalt, climate conditions and equipment cannot be anticipated by MAINTENANCE INC. The decision to use any of these methods and techniques is entirely at the election and responsibility of the user.

Warranty and Disclaimer: There are no express warranties which extend beyond the description on the face hereof. **SELLER DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR ANY PARTICULAR PURPOSE.** Since Seller cannot control the manner or use of its products after their sale, Seller will not be responsible for any consequential or indirect damages. Rather, Seller will, at its option either replace the products sold or refund the purchase price. No warranties will apply if the products are in any way altered or modified after delivery by Seller.